

Technical Data Sheet

StoBallotini Ø 75-150 µm

Solid glass beads for slip resistance Ø 75 - 150 μm



Characteristics		
Area of application	 As an admixture to StoPox or StoPur products in accordance with the relevant Technical Data Sheet 	
Properties	Transparent solid glass beads as extenders to achieve slip-resistant sealed surfaces	
Appearance	 Transparent 	
Application		
Application	By roller, add to the total mixture	
Delivery		
Packaging	Name	Container
	Sto Ballotini 75-150 µm	5 kg pail
Special Notes		
	The information in this Technical Data Sheet serves to ensure the product's intended use, or its suitability for use, and is based on our findings and experience. Users are nevertheless responsible for establishing the product's suitability and use.	
	Applications not specifically mentioned in this Technical Data Sheet are permissible only after prior consultation. Where no approval is given, such applications are at the user's own risk. This applies in particular when the product is used in combination with other products.	
	When a new Technical Data Sheet is published, all previous Technical Data Sheets are no longer valid. The latest version is available on www.sto-sea.com .	

Sto SEA Pte Ltd

159 Sin Ming Road #06-02 Amtech Building Singapore 575625 Phone: +65 6453 3080 Fax: +65 6453 3543 info.sg@sto.com www.sto-sea.com

Sto SEA Sdn Bhd

28, Jalan Rajawali 3 Bandar Puchong Jaya, 47170 Selangor, Malaysia Phone: +60 3 8080 9066 Fax: +60 3 8080 9255 info.my@sto.com www.sto-sea.com

Sto SEA Pte Ltd

3656/49-52 Green Tower, 16th Floor Rama IV Rd, Klongton, Klongtoei, 10110 Bangkok, Thailand Phone: +66 2 1684 921 Ext. 230 Fax: +66 2 1684 999 info.sq@sto.com www.sto-sea.com

StoCretec GmbH

Gutenbergstr. 6 65830 Kriftel, Germany Phone: +49 6192 401 104 Fax: +49 6192 401 105 info.sq@sto.com www.sto-sea.com

^{*}Product images may differ from the actual product.