

## Technical Data Sheet

# StoDivers GF Net CSM

Glass fiber chopped strand mat



### Characteristics

<b>Area of application</b>	StoDivers GF Net CSM is designed to provide strong reinforcement for : <ul style="list-style-type: none"> <li>▪ Most waterproofing emulsion</li> <li>▪ Crack bridging properties of the waterproofing layer</li> <li>▪ Joints on pre-fabricated panel wall, dry wall, plaster ceiling</li> <li>▪ Repair of cracks</li> </ul>
----------------------------	--

<b>Properties</b>	<ul style="list-style-type: none"> <li>▪ Light weight</li> <li>▪ High Tensile Strength</li> <li>▪ Randomly oriented, provide excellent strand integrity</li> <li>▪ Easily moulded around flashing, protrusions, joints, corners and other surface detail</li> <li>▪ Seamless application</li> <li>▪ Good Wetting properties</li> </ul>
-------------------	--

### Technical Data

Criteria	Standard / test specification	Value / Unit	Notes
Density		100 ± 10 g/m <sup>2</sup>	
Binder Content		6 ± 1 %	
Moisture Content		≤ 0.2%	
Tensile Vertical		≥ 100 N/150mm	
Tensile Horizontal		≥ 200 N/150mm	

The characteristic values stated are average values or approximate values. Due to the natural raw materials in our products, the stated values can vary slightly in the same delivery batch; this does not affect the suitability of the product for its intended use.

### Application

<b>Application temperature</b>	Lowest application temperature: +8°C
	Highest application temperature: +45°C

### Delivery

<b>Colour</b>	White
---------------	-------

Packaging	Name	Packing
	StoDivers GF Net CSM	1 m x 50 m roll

## Technical Data Sheet

# StoDivers GF Net CSM

### Storage

**Storage conditions** Store in cool dry conditions; avoid direct sunlight.

**Storage life** This product has a shelf life of 12 months from the manufacturing date.

### Identification

**Product group** Waterproofing

**Safety** Please refer to Safety Data Sheet.

### Special Notes

The information in this Technical Data Sheet serves to ensure the product's intended use, or its suitability for use, and is based on our findings and experience. Users are nevertheless responsible for establishing the product's suitability and use.

Applications not specifically mentioned in this Technical Data Sheet are permissible only after prior consultation. Where no approval is given, such applications are at the user's own risk. This applies in particular when the product is used in combination with other products.

When a new Technical Data Sheet is published, all previous Technical Data Sheets are no longer valid. The latest version is available on [www.sto-sea.com](http://www.sto-sea.com).

**Sto SEA Pte Ltd**  
159 Sin Ming Road  
#06-02 Amtech Building  
Singapore 575625  
Phone: +65 6453 3080  
Fax : +65 6453 3543  
[info.sg@sto.com](mailto:info.sg@sto.com)  
[www.sto-sea.com](http://www.sto-sea.com)

**Sto SEA Sdn Bhd**  
28, Jalan Rajawali 3  
Bandar Puchong Jaya,  
47170 Selangor, Malaysia  
Phone: +60 3 8080 9066  
Fax: +60 3 8080 9255  
[info.my@sto.com](mailto:info.my@sto.com)  
[www.sto-sea.com](http://www.sto-sea.com)

**Sto SEA Pte Ltd**  
3656/49-52 Green Tower, 16<sup>th</sup> Floor  
Rama IV Rd, Klongton, Klongtoei,  
10110 Bangkok, Thailand  
Phone: +66 2 1684 921 Ext. 230  
Fax: +66 2 1684 999  
[info.sg@sto.com](mailto:info.sg@sto.com)  
[www.sto-sea.com](http://www.sto-sea.com)

**StoCretec GmbH**  
Gutenbergstr. 6  
65830 Kriftel,  
Germany  
Phone: +49 6192 401 104  
Fax: +49 6192 401 105  
[info.sg@sto.com](mailto:info.sg@sto.com)  
[www.sto-sea.com](http://www.sto-sea.com)

\*Product images may differ from the actual product.