

Technical Data Sheet

StoCrete PU SM / HD ACC

Accelerator for low temperatures

Characteristics

Area of application ▪ For use with StoCrete PU SM & StoCrete PU HD under low temperature conditions

Properties ▪ Accelerates and reduces the curing time in cold conditions / weather
 ▪ Liquid form for ease of application

Technical Data

Temperature	Percentage	Notes
~ 10°C	1%	(30g in 3kg Part 1)
≤ 15°C	0.5%	(15g in 3kg Part 1)
≤ 20°C	0.3%	(9g in 3kg Part 1)

The characteristic values stated are average values or approximate values. Due to the natural raw materials in our products, the stated values can vary slightly in the same delivery batch; this does not affect the suitability of the product for its intended use.

Application

Material preparation StoCrete PU SM / HD ACC is added directly into Part 1 base on the application temperature mentioned in the Technical Data section.
 For example at approximately 10°C application temperature, 1% (30g) of StoCrete PU SM / HD ACC is added into 3kg of Part 1.

Delivery

Packaging	Name	Packing
	StoCrete PU SM / HD ACC	1 kg

Storage

Storage conditions Store in cool dry conditions; avoid direct sunlight.

Storage life This product has a shelf life of 24 months from the manufacturing date.

Identification

Product group Mortar

Safety Please refer to Safety Data Sheet.

Technical Data Sheet

StoCrete PU SM / HD ACC

Special Notes

The information in this Technical Data Sheet serves to ensure the product's intended use, or its suitability for use, and is based on our findings and experience. Users are nevertheless responsible for establishing the product's suitability and use.

Applications not specifically mentioned in this Technical Data Sheet are permissible only after prior consultation. Where no approval is given, such applications are at the user's own risk. This applies in particular when the product is used in combination with other products.

When a new Technical Data Sheet is published, all previous Technical Data Sheets are no longer valid. The latest version is available on www.sto-sea.com.

Sto SEA Pte Ltd
159 Sin Ming Road
#06-02 Amtech Building
Singapore 575625
Phone: +65 6453 3080
Fax : +65 6453 3543
info.sg@sto.com
www.sto-sea.com

Sto SEA Sdn Bhd
28, Jalan Rajawali 3
Bandar Puchong Jaya,
47170 Selangor, Malaysia
Phone: +60 3 8080 9066
Fax: +60 3 8080 9255
info.my@sto.com
www.sto-sea.com

Sto SEA Pte Ltd
3656/49-52 Green Tower, 16th Floor
Rama IV Rd, Klongton, Klongtoei,
10110 Bangkok, Thailand
Phone: +66 2 1684 921 Ext. 230
Fax: +66 2 1684 999
info.sg@sto.com
www.sto-sea.com

StoCretec GmbH
Gutenbergstr. 6
65830 Kriftel,
Germany
Phone: +49 6192 401 104
Fax: +49 6192 401 105
info.sg@sto.com
www.sto-sea.com

*Product images may differ from the actual product.